



RELIKCS FURNITURE

TIMBRE STEREO CONSOLE

TECHNICAL SPECIFICATIONS

AMPLIFIER

Speaker Power	Stereo: 2x50W @ 4ohm load at 21V Mono: 100W @ 2ohm load at 24V
Connectivity	WiFi: IEEE802.11 b/g/n 2.4G Bluetooth: 5.0 SBC/AAC, 15M, BT Receiver
Amplifier Chip	TPA3116D2
Frequency Response	20Hz - 20kHz
SNR/THD+N	91dB/0.03%, @1kHz 50W+50W 24V-4Ω
Audio Format	Decoding up to 192khz/24bits
Supported Protocols	AirPlay, DLNA, UPnP, Spotify Connect, Qplay
Manufacturer Information	Rakoit Up2Stream Series with Linkplay Wireless Chip

SPEAKERS

Power Handling (RMS)	100 Watts
Frequency Response	45Hz - 20kHz
Drivers	Woofer: 8" Carbon Fiber Cone Mid-range: 4" Carbon Fiber Cone Tweeter: 1" Silk Dome with Built-in Attenuator
Crossover Frequencies	490Hz and 4.6kHz
Nominal Impedance	8Ω
Sensitivity	89db

Technical Specifications

Resonant Frequency	44.269Hz
DC Resistance	7.2Ω
Suspension Control	0.457
Air Volume	40.187 liters
Linear Extrusion	3.00mm
Manufacturer P/N	Product # 34200

TURNTABLE

Tonearm	OA3 Molded Magnesium with Steel Counterweight and Internal Anti-Skate
Speed Control	Electronic
Motor	24v AC
Drive	Silicone Rubber Seamless Molded Belt
Platter	Machined Grooved Frosted Acrylic
Preamp/Phono Stage	RIAA Equalization, 40db Gain @ 1kHz, Subsonic Filter with WIMA Capacitors
Input Impedance	447kΩ
S/N Ratio	90db
Crosstalk	-89db
Slipmat	Custom 21oz FattEZ
Cartridge & Stylus	Ortofon 2M Red as Standard

WARNING for California residents: This product can expose you to chemicals including DEHP, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov